

| <i>Imperial</i> | <i>7600HD</i> | <i>8000HD</i> | <i>8600HD</i> | <i>9000HD</i> |
|----------------------------|--|--|--|--|
| Moldboard Options | Powder-Coated Steel | Powder-Coated Steel | Powder-Coated Steel | Powder-Coated Steel |
| Blade Type | Straight Blade | Straight Blade | Straight Blade | Straight Blade |
| Vehicle Compatibility | Class 2-5 Trucks & 3-4 Series Tractors | Class 2-5 Trucks & 3-4 Series Tractors | Class 2-5 Trucks & 3-4 Series Tractors | Class 2-5 Trucks & 3-4 Series Tractors |
| Approx. Weight* | 730 lbs | 746.5 lbs | 763.5 lbs | 781.5 lbs |
| Plowing Width (Straight) | 90" 110.5" (W/ Wings) | 96" 116.5" (W/ Wings) | 102" 122.5" (W/ Wings) | 108" 128.5" (W/ Wings) |
| Plowing Width (Full Angle) | 78.1" 95.2" (W/ Wings) | 83.3" 100.4" (W/ Wings) | 88.5" 105.6" (W/ Wings) | 93" 112" (W/ Wings) |
| Blade Width | 7'6" | 8'0" | 8'6" | 9'0" |
| Blade Height | 31" | 31" | 31" | 31" |
| Angle Cylinders | 1½" | 1½" | 1½" | 1½" |
| Cutting Edge | ½" x 6" (Standard) | ½" x 6" (Standard) | ½" x 6" (Standard) | ½" x 6" (Standard) |
| Blade Thickness | 12 ga | 12 ga | 12 ga | 12 ga |
| Reinforcement Ribs | 6 vertical/2 angle | 6 vertical/2 angle | 6 vertical/2 angle | 6 vertical/2 angle |
| Trip Springs | 4 steel | 4 steel | 4 steel | 4 steel |

| <i>Metric</i> | <i>7600HD</i> | <i>8000HD</i> | <i>8600HD</i> | <i>9000HD</i> |
|----------------------------|--|--|--|--|
| | 7600HD | 8000HD | 8600HD | 9000HD |
| Moldboard Options | Powder-Coated Steel | Powder-Coated Steel | Powder-Coated Steel | Powder-Coated Steel |
| Blade Type | Straight Blade | Straight Blade | Straight Blade | Straight Blade |
| Vehicle Compatibility | Class 2-5 Trucks & 3-4 Series Tractors | Class 2-5 Trucks & 3-4 Series Tractors | Class 2-5 Trucks & 3-4 Series Tractors | Class 2-5 Trucks & 3-4 Series Tractors |
| Approx. Weight* | 331 kg | 338 kg | 346 kg | 354 kg |
| Plowing Width (Straight) | 228.6 cm 280.7 cm (W/ Wings) | 243.8 cm 295.9 cm (W/ Wings) | 259.1 cm 311.2 cm (W/ Wings) | 274.3 cm 326.4 cm (W/ Wings) |
| Plowing Width (Full Angle) | 198.4 cm 241.8 cm (W/ Wings) | 211.6 cm 255 cm (W/ Wings) | 224.8 cm 268.2 cm (W/ Wings) | 236.2 cm 284.5 cm (W/ Wings) |
| Blade Width | 228.6 cm | 243.8 cm | 259.1 cm | 274.3 cm |
| Blade Height | 78.7 cm | 78.7 cm | 78.7 cm | 78.7 cm |
| Angle Cylinders | 3.8 cm | 3.8 cm | 3.8 cm | 3.8 cm |
| Cutting Edge | 1.3 cm x 15.2 cm (Standard) | 1.3 cm x 15.2 cm (Standard) | 1.3 cm x 15.2 cm (Standard) | 1.3 cm x 15.2 cm (Standard) |
| Blade Thickness | 12 ga | 12 ga | 12 ga | 12 ga |
| Reinforcement Ribs | 6 vertical/2 angle | 6 vertical/2 angle | 6 vertical/2 angle | 6 vertical/2 angle |
| Trip Springs | 4 steel | 4 steel | 4 steel | 4 steel |

*Does not include vehicle mount (28 lb - 145 lb weight range). Please refer to the Power Match program for specific vehicle applications.