

Standard-equipment

| Imperial | SD-600-1 |
|-----------------|---|
| Top Screen | 1/4" steel rod construction with grid pattern |
| Cover | Fitted lid |
| Vibrator | Standard |
| Inverted | Patented vibrating baffle to maximize material flow |

| Metric | SD-600-1 |
|---------------|---|
| Top Screen | 0.6 cm steel rod construction with grid pattern |
| Cover | Fitted lid |
| Vibrator | Standard |
| Inverted | Patented vibrating baffle to maximize material flow |

Electrical

| Imperial | SD-600-1 |
|-----------------|---|
| Speed Control | Digital, self-diagnosing variable-speed control |
| Wiring Harness | Completely loomed with molded plugs |

| Metric | SD-600-1 |
|----------------|---|
| Speed Control | Digital, self-diagnosing variable-speed control |
| Wiring Harness | Completely loomed with molded plugs |

Operational

| Imperial | SD-600-1 |
|-------------------|-----------------|
| Capacity (Volume) | 6.0 cu ft |
| Capacity (Weight) | 480 lb |
| Spreading Width | 36" |

| Metric | SD-600-1 |
|-------------------|-----------------|
| Capacity (Volume) | 0.169 cu m |
| Capacity (Weight) | 217.7 kg |
| Spreading Width | 91.44 cm |

Dimensions

| Imperial | SD-600-1 |
|------------------------|-----------------|
| Approx. Weight (Empty) | 175 lb |
| Overall Length | 24" |
| Overall Height | 28" |
| Overall Width | 49.5" |
| Hopper Length | 20.25" |
| Hopper Width | 48" |

| Metric | SD-600-1 |
|------------------------|-----------------|
| Approx. Weight (Empty) | 79.4 kg |
| Overall Length | 61.0 cm |
| Overall Height | 71.1 cm |
| Overall Width | 125.7 cm |
| Hopper Length | 51.4 cm |
| Hopper Width | 121.9 cm |