

## Dimensions

<b>Imperial</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Empty Weight	106 lb	141 lb
Overall Length	20½"	21"
Overall Height	35"	40"
Overall Width	38"	52"
Hopper Length	20½"	21"
Hopper Width	38"	47½"

<b>Metric</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Empty Weight	48.1 kg	63.9 kg
Overall Length	52.1 cm	53.3 cm
Overall Height	88.9 cm	101.6 cm
Overall Width	96.5 cm	132.1 cm
Hopper Length	52.1 cm	53.3 cm
Hopper Width	96.5 cm	120.7 cm

**Operational**

<b>Imperial</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Capacity (Volume)	5.75 cu ft	10.75 cu ft
Capacity (Weight)	460 lb	860 lb
Spreading Width	Up to 40'	Up to 40'

<b>Metric</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Capacity (Volume)	0.163 cu m	0.304 cu m
Capacity (Weight)	208.7 kg	390.1 kg
Spreading Width	Up to 12.2 m	Up to 12.2 m

**Electrical**

<b>Imperial</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Speed Control	Digital, self diagnosing variable speed control	Digital, self diagnosing variable speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

<b>Metric</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Speed Control	Digital, self diagnosing variable speed control	Digital, self diagnosing variable speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

## Construction

<b>Imperial</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	10" nylon/glass reinforced resin	10" nylon/glass reinforced resin
Auger	3" vertical high-flow auger	3" vertical high-flow auger
Mounting	Receiver mount standard. Other mounts optional.	Mount not included. (Receiver, 3-point or pivot mount optional)

<b>Metric</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	25.4 cm nylon/glass reinforced resin	25.4 cm nylon/glass reinforced resin
Auger	7.6 cm vertical high-flow auger	7.6 cm vertical high-flow auger
Mounting	Receiver mount standard. Other mounts optional.	Mount not included. (Receiver, 3-point or pivot mount optional)

**Standard Equipment**

<b>Imperial</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Top Screen	1/4" steel rod construction with grid pattern	1/4" steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Optional	Optional

<b>Metric</b>	<b>SP-575X</b>	<b>SP-1075X</b>
Top Screen	0.6 cm steel rod construction with grid pattern	0.6 cm steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Optional	Optional