

## Dimensions

<b>Imperial</b>	<b>SD-600</b>	<b>SD-1400</b>
Empty Weight	175 lb	375 lb
Overall Length	24"	30"
Overall Height	28"	38"
Overall Width	49½"	60"
Hopper Length	20¼"	24¼"
Hopper Width	48"	59"

<b>Metric</b>	<b>SD-600</b>	<b>SD-1400</b>
Empty Weight	79.4 kg	170.1 kg
Overall Length	61.0 cm	76.2 cm
Overall Height	71.1 cm	96.5 cm
Overall Width	125.7 cm	152.4 cm
Hopper Length	51.4 cm	61.6 cm
Hopper Width	121.9 cm	150.8 cm

**Operational**

<b>Imperial</b>	<b>SD-600</b>	<b>SD-1400</b>
Capacity (Volume)	6.0 cu ft	14.0 cu ft
Capacity (Weight)	480 lb	1,120 lb
Spreading Width	38"	48"

<b>Metric</b>	<b>SD-600</b>	<b>SD-1400</b>
Capacity (Volume)	0.169 cu m	0.396 cu m
Capacity (Weight)	217.7 kg	508.0 kg
Spreading Width	96.5 cm	121.9 cm

**Electrical**

<b>Imperial</b>	<b>SD-600</b>	<b>SD-1400</b>
Speed Control	Digital, self-diagnosing variable-speed control	Digital, self-diagnosing variable-speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

<b>Metric</b>	<b>SD-600</b>	<b>SD-1400</b>
Speed Control	Digital, self-diagnosing variable-speed control	Digital, self-diagnosing variable-speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

**Construction**

<b>Imperial</b>	<b>SD-600</b>	<b>SD-1400</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Mounting	Mount not included. (Receiver, 3-point or Utility mount optional)	Category I, 3-point mount standard

<b>Metric</b>	<b>SD-600</b>	<b>SD-1400</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	12-volt DC motor mounted in weather resistant enclosure	12-volt DC motor mounted in weather resistant enclosure
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Mounting	Mount not included. (Receiver, 3-point or Utility mount optional)	Category I, 3-point mount standard

**Standard Equipment**

<b>Imperial</b>	<b>SD-600</b>	<b>SD-1400</b>
Top Screen	1/4" steel rod construction with grid pattern	1/4" steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Standard	Standard
Inverted	Patented vibrating baffle to maximize material flow	Patented vibrating baffle to maximize material flow

<b>Metric</b>	<b>SD-600</b>	<b>SD-1400</b>
Top Screen	0.6 cm steel rod construction with grid pattern	0.6 cm steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Standard	Standard
Inverted	Patented vibrating baffle to maximize material flow	Patented vibrating baffle to maximize material flow