

Dimensions

| Imperial | SD-600-1 |
|-----------------|-----------------|
| Empty Weight | 175 lb |
| Overall Length | 24" |
| Overall Height | 28" |
| Overall Width | 49½" |
| Hopper Length | 20¼" |
| Hopper Width | 48" |

| Metric | SD-600-1 |
|----------------|-----------------|
| Empty Weight | 79.4 kg |
| Overall Length | 61.0 cm |
| Overall Height | 71.1 cm |
| Overall Width | 125.7 cm |
| Hopper Length | 51.4 cm |
| Hopper Width | 121.9 cm |

Operational

| Imperial | SD-600-1 |
|-------------------|-----------------|
| Capacity (Volume) | 6.0 cu ft |
| Capacity (Weight) | 480 lb |
| Spreading Width | 38" |

| Metric | SD-600-1 |
|-------------------|-----------------|
| Capacity (Volume) | 0.169 cu m |
| Capacity (Weight) | 217.7 kg |
| Spreading Width | 96.5 cm |

Electrical

| Imperial | SD-600-1 |
|-----------------|-------------------------------------------------|
| Speed Control | Digital, self-diagnosing variable-speed control |
| Wiring Harness | Completely loomed with molded plugs |

| Metric | SD-600-1 |
|----------------|-------------------------------------------------|
| Speed Control | Digital, self-diagnosing variable-speed control |
| Wiring Harness | Completely loomed with molded plugs |

Construction

| Imperial | SD-600-1 |
|----------------------|----------------------------------------------------------------------------------|
| Frame | Powder coated steel |
| Hopper | One-piece LLDPE safety yellow poly |
| Motors | 12-volt DC motor mounted in weather resistant enclosure |
| Auger Drive Assembly | Heavy-duty solid steel construction with maximum-torque motor transmission drive |
| Mounting | Mount not included. (Receiver, 3-point or Utility mount optional) |

| Metric | SD-600-1 |
|----------------------|----------------------------------------------------------------------------------|
| Frame | Powder coated steel |
| Hopper | One-piece LLDPE safety yellow poly |
| Motors | 12-volt DC motor mounted in weather resistant enclosure |
| Auger Drive Assembly | Heavy-duty solid steel construction with maximum-torque motor transmission drive |
| Mounting | Mount not included. (Receiver, 3-point or Utility mount optional) |

Standard Equipment

| Imperial | SD-600-1 |
|-----------------|-----------------------------------------------------|
| Top Screen | 1/4" steel rod construction with grid pattern |
| Cover | Fitted lid |
| Vibrator | Standard |
| Inverted | Patented vibrating baffle to maximize material flow |

| Metric | SD-600-1 |
|---------------|-----------------------------------------------------|
| Top Screen | 0.6 cm steel rod construction with grid pattern |
| Cover | Fitted lid |
| Vibrator | Standard |
| Inverted | Patented vibrating baffle to maximize material flow |